

SUTOP EBT-ASTAR

Bitumen Based Primer

AREA OF USE

It's used as primer before using bituminous membrane or bituminous splash based waterproofing material in indoors and outdoors, on horizontal and vertical surfaces. It's also used as vapor barrier waterproofing layer for insulation and protection of concrete surfaces. In addition it can be used on retaining walls, terraces, silos, warehouses and building external walls.

PROPERTIES

- Single component.
- Through its superior adhesion property, it provides bituminous materials on it to be adhered on surface more robust.
- Ready to use, easy to apply to the surface.
- It is water based, so it is environmentally friendly.
- It does not contain flammable and toxic substances that can be safely used indoors.
- It's applied as cold, doesn't require thinning.

APPLICATION

The surface to be implemented should be clean, free from dust and balanced. Surface must be free from all contaminants such as dust, paint, surface mold oil, and must be cured.

If there are cracks and holes on the surface before application, they must be filled.

CONSUMPTION

About 0,5 kg/m² for a single coat.(2-3 coats are applied)

TECHNICAL DATA

Colour	Brown, Black
Density	1.00 ± 0.01 kg/lt
pH	10,5-11,5
Viscosity	20 d Pa.s
Solids	36.0 % ± 1.00 %
Temperature of the Surface to be applied	+5 °C / +30 °C
First Drying Time	4-5 hours
Completely Drying Time	1 – 3 days

PACKAGING AND STORAGE

- It's stored in 15 liters of plastic buckets.
- Up to 3 buckets can be stacked on each other.
- Under proper storage conditions, its shelf life is 1 year from date of production.
- It should be kept cool and dry on wood pellets.

WARNINGS

- It must be protected against water and heavy weather conditions.
- Torn and opened packagings must be immediately closed and consumed first.
- Application must not be made on rainy weather and on wet surfaces.
- Application is advisable in temperature of +5 ° C to +35 ° C.
- Do not apply under direct sunlight.
- Do not exceed the specified instructions and application surface.
- Do not inhale. In case of flush contact with eyes, flush with plenty of water, seek medical advice if necessary.
- Ask for product safety data sheet for more information.
- Please consult us for your technical questions related to all other application conditions.

CERTIFICATE OF CONFORMITY



The above data were obtained in the laboratory. For more information, please consult our Technical Department.
Entegre reserves the right to change the above information.
Entegre is not responsible for any failure due to misapplication.