SUTOP EBT-1N

Polymer-Modified Bitumen Emulsion Waterproofing Material

(Moisture Barrier)

WATERPROOFING SOLUTIONS

Areas of Use

- Foundation and basement walls.
- Garden and retaining walls.
- Protection against dampness and moisture.

Properties

- Easy to prepare and apply.
- Fully adheres to the substrate.
- Water-based and environmentally friendly.
- UV resistance is limited; the coating must be covered after application.

Application

Surface Preparation

The substrate must be sound and free from oil, grease, rust, paraffin, paint, bitumen residues and any other materials that may prevent adhesion. Remove all loose particles. To improve adhesion, prime the substrate with SUTOP® EBT-1N diluted with water at a ratio of 1:5. Allow the primer to dry before applying the product.

Application Conditions

- Do not apply to frozen surfaces.
- The substrate must be dry and free from dust and materials that prevent adhesion.
- Take the necessary precautions in areas where water or water vapour is present on the negative side.
- Before application, check substrate moisture and adhesion, and determine the dew point.
- This product must be applied only by experienced professionals.
- Refer to the safety data sheet for further information.

Application Details

Mix the product with a mixer operating at 400–600 rpm until a homogeneous mixture is obtained (approximately 5 minutes). Use the mixture without prolonged delay and consume it within 1–2 hours. Apply the prepared material to the primed substrate.

Liability: Above stated data obtained in lab conditions. Entegre will not be liable for any defect in product occurring by reason of events or conditions not within its control such as misuse, mishandling, improper storage or improper installation. Entegre reserves the right to revise the information contained herein without prior notice.

Hüseyinli Mah. Beykoz Cad. No: 222/4 Çekmeköy - İstanbul
+90 (0216) 434 50 96
export@entegreharc.com.tr

Consumption

Consumption for a minimum of 2 coats is 1.5–2 kg/m^2. (May vary depending on substrate characteristics and application conditions.)

Packaging and Storage

- 18 kg plastic bucket.
- Shelf life is 12 months in unopened packaging stored away from sunlight.

Warnings

- Protect from water, frost and severe weather conditions.
- Damaged or opened containers must be closed immediately and used first.
- Application at temperatures between +5 °C and +30 °C is recommended.
- Observe the storage conditions during transport.
- Do not leave unapplied product in direct sunlight.
- Do not use outside the specified areas of use or contrary to the application instructions.
- Do not inhale directly.
- In case of contact with eyes, rinse with plenty of water and seek medical advice if necessary.
- Request the product safety data sheet for further information.
- Contact us for technical questions and all other application conditions.

Liability: Above stated data obtained in lab conditions. Entegre will not be liable for any defect in product occurring by reason of events or conditions not within its control such as misuse, mishandling, improper storage or improper installation. Entegre reserves the right to revise the information contained herein without prior notice.

ENTEGRE
Hüseyinli Mah. Beykoz Cad.
No: 222/4 Çekmeköy - İstanbul
+90 (0216) 434 50 96
export@entegreharc.com.tr