



# MATERIAL SAFETY DATA SHEET

## PRİMEL 600 (BETOKONTAK)

Printed On: 01.06.2016

Revision No:02

### **1. IDENTIFICATION OF THE SUBSTANCE/ MIXTURE AND OF THE COMPANY/UNDERTAKING**

#### **1.1. Product Identifier**

**Product Name:** Primel 600 (Betokontak)

**Intended Use:** Acrylic based adhesion enhancing primer

#### **1.2. Details of the supplier of the safety data sheet**

**Company Name:** Entegre Harç San ve Tic. A. Ş.

**Address:** Hüseyinli Köyü Beykoz Cad. No:222/4 34799 Çekmeköy / İstanbul

**Phone:** + 90 216 434 50 96

**Fax:** + 90 216 434 63 89

**E-Mail:** [info@entegreharc.com.tr](mailto:info@entegreharc.com.tr)

#### **1.3. Emergency Phone Number**

**Company Number** + 90 216 434 50 96

### **2. HAZARD IDENTIFICATION**

#### **2.1. Classification of the substance or mixture**

It does not have health and physical damage.

It is not dangerous for the environment. However, it is not appropriate to dispose of the product packaging in the sewer system, water discharge systems and the environment.

#### **2.2. Label Elements**

It is out of scope

#### **2.3. Other Hazards**

All of the threads with the hazard statements are given in Section 16.

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### **3.1. Materials**

No dangerous component

#### **3.2. Mixtures**

Acrylic resin dispersion

### **4. FIRST AID MEASURES**

#### **4.1. General Recommendations**

Consult a physician. Show this safety data sheet to the physician.

#### **4.2. Inhalation**

Move to the fresh air. Give artificial respiration if necessary. If necessary seek medical advice.

#### **4.3. Eye Contact**

Immediately rinse with water for a prolonged period whilst keeping the eyes wide open.



# MATERIAL SAFETY DATA SHEET

## PRİMEL 600 (BETOKONTAK)

Printed On: 01.06.2016

Revision No:02

### 4.4. Skin Contact

Immediately rinse with plenty of water.

### 4.5. Ingestion

Rinse mouth. Never give an unconscious person anything to drink.

## 5. FIREFIGHTING MEASURES

### 5.1 General Information

The product is not spontaneously flammable show feature.

### 5.2. Suitable Extinguishing Media

Use sand, alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>) or water-spray.

### 5.3. Special hazards arising from the substance or mixture

Carbon dioxide

### 5.4. Advice for firefighting

In case of fire, wear suitable respiratory equipment with positive air supply.

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions,

Personal protective equipments are used.

### 6.2. Environmental precautions

Prevent leaks and spills. Do not discharge into the drains. Discharge into the environment must be avoided.

### 6.3. Methodes for celaning up

Absorb the liquid binder with dust (sand, diatomite, acid binders, universal binders, sawdust).

Collect in the appropriate container for large quantities of debris. If not used, dispose of it.

Pick up mechanically, avoiding dust, and provide disposal in suitable recipients.

## 7. HANDLING AND STORAGE

### 7.1. Handling

Avoid contact with eyes and skin.

### 7.2. Storage

The product must be protected from moisture and bad weather to protect its qualities and properties.

Protect from freezing. Protect from the sun.

Packaging should be stored tightly closed in a dry and well-ventilated place.



# MATERIAL SAFETY DATA SHEET

## PRİMEL 600 (BETOKONTAK)

Printed On: 01.06.2016

Revision No:02

### **8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### **8.1. Exposure Limits**

STEL / TWA: Not detected

#### **8.2 Personal Protective Equipment**

Foodstuffs, Keep away from drink and animal feed. Contaminated, remove immediately all contaminated clothing, reuse of wash. Wash your hands after work and the work of breaks. Gloves must be inspected regularly and prior to each use.

#### **Respiratory -related precautionary measures**

In cases where ventilation is insufficient to use respiratory protective equipment should be considered.

#### **Hand protection**

Gloves should be selected in accordance with a standard pharmaceutically acceptable carrier.

#### **Eye protection**

Use chemical safety glasses with side shields

#### **Body protection**

Use protective clothing.

### **9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: Viscous, Pink

Odour: Light smell

pH: 7-9

Flammability: Not applicable

Solubility in water: Soluble in water

Density (20 °C): ~1,5 g/m<sup>3</sup>

### **10. STABILITY AND REACTIVITY**

#### **10.1. Stability**

Stable at ambient temperature and under normal conditions of use.

#### **10.2. Hazardous Reactions**

If used according to the technical specification, no deterioration will occur.

There is no known degradation product.



# MATERIAL SAFETY DATA SHEET

## PRİMEL 600 (BETOKONTAK)

Printed On: 01.06.2016

Revision No:02

### **11. TOXICOLOGICAL INFORMATION**

#### **11.1. Information on Toxic Effects**

The product is not classified in accordance with the method of calculation of the General EC Classification Guidelines for Preparations as issued in the latest version.

When used in accordance with specifications, the product does not have any harmful effects on the basis of our experience and the information provided to us.

There is no known sensitizing effect.

#### **11.2 Impact on Health:**

In case of inhalation, there is no irritant effect.

No irritant effect on skin. In the eyes, slight irritation is possible.

Sensitivity studies have not been performed on the mixture. According to the compositions, it is unlikely that the mixture is susceptible to sensitization.

#### **11.3. Toxicological Warnings:**

Product was not tested. Toxicological classification of content information is made based on information available and obtained.

### **12. ECOLOGICAL INFORMATION**

#### **12.1. Ecotoxicity**

Prevent the product from reaching water sources, sewage systems or sewage systems.

No ecological work is available. So far, no harmful effects on human and environment have been observed. When used as intended, does not have any environmental poisoning effect according to available information.

#### **12.2 Persistence and Biodegradability**

It is invalid.

### **13. DISPOSAL CONSIDERATIONS**

#### **WASTE FROM RESIDUES:**

Destruction/Disposal: Solid waste: Incinerate.

Liquid waste: Decant and separate solid material prior to disposal. Dispose of solid residues at a licensed site.

Small quantities: allow the product to dry then incinerate solid residues at an approved site.

#### **CONTAMINATED PACKAGING:**

Decontamination/cleaning: Empty the packaging completely prior to disposal.

Destruction/Disposal: Incinerate bags and flexible containers.



# MATERIAL SAFETY DATA SHEET

## PRİMEL 600 (BETOKONTAK)

Printed On: 01.06.2016

Revision No:02

NOTE: The user's attention is drawn to the possible existence of local regulations regarding disposal.

### **14. TRANSPORT INFORMATION**

Air, Sea Rail/ Road: NOT restricted.

### **15. REGULATORY INFORMATION**

National and international regulations must be complied with .  
Refer to section 2 of this document for labeling information.

### **16. OTHER INFORMATION**

#### **16.1 Additional Info**

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfil his obligations regarding the use of hazardous products. This information is not exhaustive. This does not exonerate the user from ensuring that legal obligations, other than those mentioned, relating to the use and storage of the product, do not exist. This is solely his responsibility.