



## TECHNICAL DATA SHEET

### **MULTIFINISH**

#### **Finishing Plaster**

#### APPLICATION FIELDS

It is used as a topcoat on wide range of materials such as gypsum or cement based plasters in interior surfaces.

#### FEATURES & BENEFITS

**Multifinish** can be applied for the finishing of low suction (Plasterboard) to medium suction (Gypsum and cement based plasters) undercoat plasters.

Provides comfortable, easy and fast application.

Multifinish has high adherence and strength values thanks to special additives.

Ensures excellent surface quality before painting.

#### SURFACE PREPARATION

Surface to be treated; mould oil, dust, paint, such as materials must be cleaned.

Before application, wide cracks and deep holes should be fixed with suitable repairing mortars.

If necessary, surface should be moistured before application.

#### APPLICATION

Firstly, add water to the mixing bowl, then add the Multifinish (approximately 11 lt water for 25 kg bag) and mix until the lumps go away. Wait 5 minutes, and mix again to obtain a homogeneous mixture. Plaster is applied to the surface by a steel trowel with a thickness of 2-3 mm. Before painting, the surface is finished with a fine sandpaper.

#### COVERAGE

10m<sup>2</sup>/bag for 2 mm thickness.

#### TECHNICAL DATA

Compressive Strength, N/mm <sup>2</sup>	≥ 6
Bond Strength, N/mm <sup>2</sup>	≥ 3
Adhesion Strength, N/mm <sup>2</sup>	> 0,3
Initial Setting Time, min	60 - 80