

Areas of Use

Used for bonding ceramic tile and wall tile coverings on horizontal and vertical surfaces indoors and in flooring applications outdoors.

It is applied over cement-based plaster on walls and over cement-based screed and concrete slabs on floors in dry and moderately wet areas.

For an ideal application, the following covering surface areas are suitable:

Indoor floors: Ceramic tile area $\leq 1600 \text{ cm}^2$

Outdoor floors: Ceramic tile area $\leq 1200 \text{ cm}^2$

Indoor walls: Ceramic tile area $\leq 1100 \text{ cm}^2$

Advantages

- Provides comfortable workability thanks to its extended pot life and skinning time.
- Has reduced slip.
- Easy to prepare.
- Can be applied to the surface very easily.

Application

Surface Preparation

The surface must be completely free of formwork oil, dust, paint and substances that reduce adhesion.

Before application, cracks and holes must be repaired with suitable Entegre repair mortars.

If necessary, the application surface must be dampened with water.

Before application on surfaces that are not resistant to moisture, such as gypsum plaster, PRİMEL 100® is applied; once drying is complete, the bonding process is started.

Mortar Preparation and Application

First, water is poured into the mixing container, and then KAROFIX PLUS® is added (6-6.5 L of water/25 kg bag) and mixed with a low-speed hand mixer until the lumps disappear. The mixture is left to stand for 5 minutes and then mixed again to obtain a homogeneous consistency. The prepared mortar is applied to the surface up to a thickness of 10 mm, combed, and the ceramic tile is bonded. For good adhesion, pressure must be applied to the surface with a rubber mallet. Double-sided bonding must be used for coverings larger than $1,100 \text{ cm}^2$. Grouting may begin at least 24 hours after the application of Karofix Plus.

ENTEGRE

"Building Life"

KAROFIX PLUS®Ready-Mixed Cement-Based
Ceramic Tile Adhesive with
Extended Open TimeTILE ADHESIVES AND
GROUTING MORTARS

Consumption

Applicable to single-sided application.

Trowel Size	Consumption (kg/m ²)
3	2-3
4	3-4
6	4-5
8	5-6
10	6-7

Document No: TDS.ENG.04.02

Revision No: 1

Validity Date: 05.08.2026

Liability: The above data were obtained under laboratory conditions. Entegre shall not be held liable for any problems or damages arising from use of the product for purposes other than those specified, failure to comply with the stated storage, preservation and application conditions, or incorrect application. Entegre reserves the right to update and amend the above information without prior notice.



Hüseyinli Mah. Beykoz Cad.
No: 222/4 Çekmeköy - İstanbul

+90 (0216) 434 50 96

export@entegreharc.com.tr

Page 2

ENTEGRE

"Building Life"

KAROFIX PLUS®Ready-Mixed Cement-Based
Ceramic Tile Adhesive with
Extended Open TimeTILE ADHESIVES AND
GROUTING MORTARS

Technical Values

Technical Values	Value
Open Time: Tensile Adhesion Strength, N/mm ² (after at least 30 minutes), (TS EN 12004-2)	≥ 0,5
Pot Life, Hours	≤ 2
Adhesion Strength; N/mm ² (TS EN 12004-2)	
Under Dry Conditions	≥ 0,5
Under Wet Conditions	≥ 0,5
Under Hot Conditions	≥ 0,5
Under Cold Conditions	≥ 0,5
Slip, mm (TS EN 12004-2)	≤ 0,5
Reaction to Fire (TS EN 13501-1)	A1

Packaging and Storage

- Supplied on pallets in 25 kg polyethylene-reinforced kraft bags.
- The shelf life is 1 year from the date of production when stored unopened in its original packaging in a dry, frost-free environment, stacked no more than 8 bags high and without direct contact with the floor; after opening the bag, consumption within 1 week is recommended.
- Keep packages tightly closed when not in use.

Warnings

- No foreign material (lime, cement, gypsum, etc.) must be added to the prepared mortar.
- Mortar whose pot life has expired must not be mixed with water or dry mortar and reused.
- Application at temperatures between +5 °C and +35 °C is recommended.
- For an ideal application, the covering material must be bonded to the mortar applied to the surface within 20 minutes.

Document No: TDS.ENG.04.02

Revision No: 1

Validity Date: 05.08.2026

Liability: The above data were obtained under laboratory conditions. Entegre shall not be held liable for any problems or damages arising from use of the product for purposes other than those specified, failure to comply with the stated storage, preservation and application conditions, or incorrect application. Entegre reserves the right to update and amend the above information without prior notice.



Hüseyinli Mah. Beykoz Cad.
No: 222/4 Çekmeköy - İstanbul

+90 (0216) 434 50 96

export@entegreharc.com.tr

Page 3

ENTEGRE

"Building Life"

KAROFIX PLUS®**Ready-Mixed Cement-Based
Ceramic Tile Adhesive with
Extended Open Time****TILE ADHESIVES AND
GROUTING MORTARS**

- Do not apply on frozen surfaces.
- Do not apply under direct sunlight.
- Do not use outside the specified application areas and instructions for use.
- Do not inhale directly. In case of contact with eyes, rinse with plenty of water and seek medical advice if necessary.
- For further information, request the product safety data sheet.
- Please consult us regarding all other application conditions and for your technical questions.

Certificate of Conformity



TS EN 12004-1 / April 2017 / C1TE

C1: Normal-Setting Cementitious Adhesive

T: Reduced Slip

E: Extended Open Time

Ministry of Public Works Item No: 10.300.2202

Document No: TDS.ENG.04.02

Revision No: 1

Validity Date: 05.08.2026

Liability: The above data were obtained under laboratory conditions. Entegre shall not be held liable for any problems or damages arising from use of the product for purposes other than those specified, failure to comply with the stated storage, preservation and application conditions, or incorrect application. Entegre reserves the right to update and amend the above information without prior notice.



Hüseyinli Mah. Beykoz Cad.
No: 222/4 Çekmeköy - İstanbul

+90 (0216) 434 50 96

export@entegreharc.com.tr