



Fields of Application

It is used as a primer before the application of ceramic adhesives, cement-based finishing plasters and skim coats on moisture-sensitive surfaces such as gypsum boards, gypsum plasters and chipboards.

It is used as a primer to prevent surface dusting and protect cement-based applications (plaster and screed).

It is used to prime aerated concrete, plaster and brick surfaces before plastering in order to prevent cracking caused by rapid water absorption.

Properties

- Provides high performance in preventing cracks.
- Improves the performance of plastering and ceramic applications on absorbent surfaces.
- Prevents dusting on cement-based plaster and screed surfaces.

Application and Consumption

Before applying ceramic adhesives, cement-based finishing plasters and skim coats on moisture-sensitive surfaces such as gypsum boards, gypsum plasters and chipboards, dilute PRİMEL 100® with water at a ratio of 1:1 for the first coat and apply the second coat undiluted by brush. Proceed with the subsequent application after complete drying.

Consumption: ~120 g/m²

To prevent surface dusting and protect cement-based applications (plaster and screed), apply by brush to the dry surface after diluting with water at a ratio of 1:3 for the first coat and 1:1 for the second coat. Proceed with the subsequent application after complete drying.

Consumption: ~100 g/m²

To prevent cracking caused by rapid water absorption before plastering, dilute with water at a ratio of 1:1 and apply by brush when priming aerated concrete, plaster and brick surfaces. Proceed with the subsequent application after complete drying.

Consumption: ~50 g/m²

ENTEGRE

"Building Life"

PRİMEL 100®**Performance-Enhancing Acrylic Resin-
Based Primer for Absorbent Surfaces****COMPLEMENTARY AND
AUXILIARY PRODUCTS**

Technical Values

Density, kg/L	≈ 1
Colour	Blue
Second Coat Application Time, Hours	2
Drying Time, Hours	2
Initial Adhesion Strength, N/mm ²	≥ 1,0

- Keep out of reach of children.
- Keep the container tightly closed.
- Avoid contact with eyes and skin.
- Please consult us regarding any other application conditions and technical questions.

Packaging and Storage

- Packaged in a 10 litre plastic container.
- Shelf life is 1 year from the date of manufacture when stored unopened in its original packaging in a dry environment protected from frost.

Warnings

- Application is recommended at temperatures between +5 °C and +35 °C.
- The application surface must be dust-free, dry and clean.
- Protect from frost.
- Wash all tools with water after application.
- Harmful if swallowed.

Certificate of Conformity



TS 13744 / March 2017

Class 2: Adhesion-Enhancing Primer without Filler

Document No: TDS.ENG.07.01

Revision No: 1

Validity Date: 20.08.2026

Liability: Above stated data obtained in lab conditions. Entegre will not be liable for any defect in product occurring by reason of events or conditions not within its control such as misuse, mishandling, improper storage or improper installation. Entegre reserves the right to revise the information contained herein without prior notice.



Hüseyinli Mah. Beykoz Cad.
No: 222/4 Çekmeköy - İstanbul

+90 (0216) 434 50 96

export@entegreharc.com.tr

Page 2