

 ENTEGRE

PRIMEL 300®

"Building Life"

Organic-Acid-Based Grout and Cement
Stain CleanerCOMPLEMENTARY AND
AUXILIARY PRODUCTS

Fields of Application

Used to clean coverings contaminated with mortar, grout and cement-based construction residues, as well as joints that have become soiled over time.

Properties

A combination of organic acids and surfactants.

Application

PRIMEL 300®/Water: Dilute at a ratio of 1:5 and apply to the surface to be cleaned. After allowing it to act for a while, clean the surface with a brush and sponge.

Consumption: Approx. 50–80 g/m².

Used for cleaning joints that have become soiled over time. For cleaning purposes, apply PRIMEL 300®, diluted again with water at a ratio of 1:5, to the joints using a suitable sponge.

Consumption: Approx. 20 g/m².

Packaging and Storage

- Packaged in 1-litre plastic containers.
- The shelf life is 1 year from the date of manufacture when stored unopened in its original packaging in a dry, frost-free environment.

Warnings

- Application is recommended at temperatures between +5 °C and +30 °C.
- Protect from frost.
- All tools used must be washed and cleaned with water after application.
- Harmful if swallowed.
- Keep out of reach of children.
- Keep in a tightly closed container.
- Avoid contact with eyes and skin.
- Please consult us regarding all other application conditions and technical questions.

Document No: TDS.ENG.07.03

Revision No: 1

Validity Date: 20.08.2026

Liability: Above stated data obtained in lab conditions. Entegre will not be liable for any defect in product occurring by reason of events or conditions not within its control such as misuse, mishandling, improper storage or improper installation. Entegre reserves the right to revise the information contained herein without prior notice.



Hüseyinli Mah. Beykoz Cad.
No: 222/4 Çekmeköy - İstanbul

+90 (0216) 434 50 96

export@entegreharc.com.tr

Page 1