

ENTEGRE

"Building Life"

PRIMEL 500®**Acrylic Resin-Based Liquid Curing
Compound Used for Concrete, Mortar
and Surface Hardeners****COMPLEMENTARY AND
AUXILIARY PRODUCTS**

Fields of Application

- Used for curing floors treated with SURFACEFIX and improving surface performance.
- Used for curing screed concrete and cast concrete.

Properties

- Prevents crack formation by preventing rapid water loss.
- Prevents dusting by increasing the surface's abrasion resistance.
- Increases water impermeability and prevents freeze cracking.

Application

After the SURFACEFIX application has been completed, apply in two coats by spraying or brushing: on cast-concrete surfaces, as soon as the surface sheen disappears; and on formed concrete, immediately after the formwork is removed.

Consumption

200–250 g/m²

Technical Values

Density, kg/L	≈0.82
Colour	White
Flash Point, °C	88
Drying Time, min	≈ 45

Packaging and Storage

- Packaged in 10-litre plastic containers.
- Store in enclosed areas away from direct sunlight.
- The shelf life is 1 year from the date of manufacture when stored unopened in its original packaging in a dry, frost-free environment.

Document No: TDS.ENG.07.05

Revision No: 1

Validity Date: 20.08.2026

Liability: Above stated data obtained in lab conditions. Entegre will not be liable for any defect in product occurring by reason of events or conditions not within its control such as misuse, mishandling, improper storage or improper installation. Entegre reserves the right to revise the information contained herein without prior notice.



Hüseyinli Mah. Beykoz Cad.
No: 222/4 Çekmeköy - İstanbul

+90 (0216) 434 50 96

export@entegreharc.com.tr

Page 1

The logo for Entegre, featuring the word "ENTEGRE" in white capital letters on a green rectangular background, which is itself on a dark grey background with a grid of small squares.

"Building Life"

PRIMEL 500®

Acrylic Resin-Based Liquid Curing
Compound Used for Concrete, Mortar
and Surface Hardeners



COMPLEMENTARY AND
AUXILIARY PRODUCTS

Warnings

- Application is recommended at temperatures between +5 °C and +30 °C.
- Protect from frost.
- Wash and clean all tools with water after application.
- Harmful if swallowed.
- Keep out of reach of children.
- Keep in a tightly closed container.
- Avoid contact with eyes and skin.
- Please consult us regarding all other application conditions and technical questions.

Document No: TDS.ENG.07.05

Revision No: 1

Validity Date: 20.08.2026

Liability: Above stated data obtained in lab conditions. Entegre will not be liable for any defect in product occurring by reason of events or conditions not within its control such as misuse, mishandling, improper storage or improper installation. Entegre reserves the right to revise the information contained herein without prior notice.



Hüseyinli Mah. Beykoz Cad. +90 (0216) 434 50 96
No: 222/4 Çekmeköy - İstanbul ✉ export@entegreharc.com.tr

Page 2