

ENTEGRE

"Building Life"

PRIMEL 100® S**Water-Repellent Solution for Exterior Surfaces**COMPLEMENTARY AND
AUXILIARY PRODUCTS

Fields of Application

Used as an impregnating coating on concrete, aerated concrete, Eternit (fibre-cement), brick, plaster and roof-tile surfaces to prevent water absorption and soiling. Provides high performance, particularly on exterior façade coatings, in the restoration of historic buildings and on floors exposed to excessive moisture.

Properties

- Reduces soiling, mould growth and wear on surfaces exposed to water.
- Protects building elements against water loading and moisture penetration.
- Resistant to alkalis and UV radiation.
- Protects exterior façade coatings against soiling.
- Has a colourless and clear appearance.

Application

Surface Preparation

The application surface must be clean, dry and free of oil. Remove aged paint and loose particles from the surface. Damp surfaces must be thoroughly dried.

Application

Apply PRIMEL 100® S to the surface from top to bottom using a brush or sprayer. Continue until the surface is fully saturated.

Consumption

Approx. 200–500 g/m² (varies depending on surface absorbency).

Technical Values

Density, kg/L	≈ 0.75
Drying Time, hours	≈ 24

Packaging and Storage

- Packaged in a 5-litre plastic container.
- The shelf life is 1 year from the date of manufacture when stored unopened in its original packaging in a dry, frost-free environment.

Document No: TDS.ENG.07.09

Revision No: 1

Validity Date: 20.08.2026

Liability: Above stated data obtained in lab conditions. Entegre will not be liable for any defect in product occurring by reason of events or conditions not within its control such as misuse, mishandling, improper storage or improper installation. Entegre reserves the right to revise the information contained herein without prior notice.



Hüseyinli Mah. Beykoz Cad.
No: 222/4 Çekmeköy - İstanbul

+90 (0216) 434 50 96

export@entegreharc.com.tr

Page 1

 ENTEGRE

PRIMEL 100® S

"Building Life"

Water-Repellent Solution for Exterior
SurfacesCOMPLEMENTARY AND
AUXILIARY PRODUCTS

Warnings

- Application is recommended at temperatures between +5 °C and +30 °C.
- The application surface must be dust-free, dry and clean.
- Protect from frost.
- Wash all tools with water after application.
- Harmful if swallowed.
- Keep out of reach of children.
- Keep in a tightly closed container.
- Avoid contact with eyes and skin.
- Please consult us regarding all other application conditions and technical questions.

Certificate of Conformity

Ministry of Public Works Item No.: 04.503/2

Document No: TDS.ENG.07.09

Revision No: 1

Validity Date: 20.08.2026

Liability: Above stated data obtained in lab conditions. Entegre will not be liable for any defect in product occurring by reason of events or conditions not within its control such as misuse, mishandling, improper storage or improper installation. Entegre reserves the right to revise the information contained herein without prior notice.



Hüseyinli Mah. Beykoz Cad. +90 (0216) 434 50 96
No: 222/4 Çekmeköy - İstanbul ✉ export@entegreharc.com.tr

Page 2