

ENTEGRE

"Building Life"

BOARDFIX®

Gypsum Board Adhesive



GYPSUM PLASTERS

Areas of Use

BOARDFIX is a gypsum-based adhesive designed for bonding and fixing gypsum boards to wall surfaces.

Advantages

- Suitable for interior applications.
- Provides easy, convenient and fast application.
- Provides high adhesion and strength thanks to the special additives in its formulation.
- BOARDFIX is classified as an A1 non-combustible material.

Application

Surface Preparation

The application surface must be free from formwork oil, dust, paint and similar substances. The application surface must be protected against moisture and kept dry.

Mortar Preparation and Application

First, water is poured into a clean mixing container, then BOARDFIX is added (approximately 13 L of water for a 25 kg bag) and mixed until all lumps are completely eliminated. Allow the mixture to stand for 5 minutes, then mix again to obtain a homogeneous consistency.

The prepared mortar is applied to the back of the gypsum board in dabs approximately 10 cm in diameter, spaced at 30-40 cm intervals. The gypsum board is then properly aligned using a spirit level and fixed by pressing it onto the wall surface.

Consumption

Approx. 4 kg/m².

Technical Values

Compressive Strength, N/mm ²	≥ 6,0
Flexural Strength, N/mm ²	≥ 3,0
Adhesion Strength, N/mm ²	≥ 0,4
Initial Setting Time, min	>50

Document No: TDS.ENG.01.06

Revision No: 1

Validity Date: 10.08.2026

Liability: Above stated data obtained in lab conditions. Entegre will not be liable for any defect in product occurring by reason of events or conditions not within its control such as misuse, mishandling, improper storage or improper installation. Entegre reserves the right to revise the information contained herein without prior notice.

ENTEGRE

"Building Life"

BOARDFIX®

Gypsum Board Adhesive



GYPSUM PLASTERS

Packaging and Storage

Gypsum-based products must be stored in a closed and dry environment. Gypsum bags must be stacked on pallets so that they do not come into contact with damp floors or walls. Long-term outdoor storage is not recommended.

All gypsum-based plasters are sensitive to varying humidity conditions and ageing over time. This may cause variations in setting time and product performance issues.

When stored under the recommended storage conditions, the products have a shelf life of 6 months from the date of production.

- For further information, request the product Safety Data Sheet.
- Please consult us regarding all other application conditions and for technical questions.

Certificate of Conformity

Complies with TS EN 14496.

Warnings

- No foreign material (lime, cement, gypsum, etc.) should be added to the prepared mortar.
- Application is recommended at temperatures between +5 °C and +35 °C.
- Do not use outside the specified areas of application or contrary to the instructions for use.
- Do not inhale directly. In case of contact with eyes, rinse with plenty of water and seek medical advice if necessary.

Document No: TDS.ENG.01.06

Revision No: 1

Validity Date: 10.08.2026

Liability: Above stated data obtained in lab conditions. Entegre will not be liable for any defect in product occurring by reason of events or conditions not within its control such as misuse, mishandling, improper storage or improper installation. Entegre reserves the right to revise the information contained herein without prior notice.

ENTEGRE

Hüseyinli Mah. Beykoz Cad.
No: 222/4 Çekmeköy - İstanbul

+90 (0216) 434 50 96

export@entegreharc.com.tr

Page 2