

ENTEGRE

"Building Life"

PRIMEL SL®**Adhesion-Enhancing, Defoaming Floor
Preparation Primer****COMPLEMENTARY AND
AUXILIARY PRODUCTS**

Fields of Application

Used as a floor-preparation primer before screed and concrete applications to prevent rapid water absorption by the substrate and increase adhesion. It is particularly recommended before self-levelling screeds.

Properties

- Compatible with FLOORSER® (3–15 mm) and FLOORSER® (3–30 mm).
- Has defoaming properties.
- Provides high adhesion.

Application

Apply by brush or spray before the flooring application. After the surface has dried, proceed with the application of FLOORSER® (3–15 mm) or FLOORSER® (3–30 mm). Apply two coats on highly absorbent surfaces.

Consumption

100–150 g/m²

Technical Values

Density, kg/L	≈1
Colour	White
Time Before Application of Second Coat, hours	≈2
Drying Time, hours	≈2
Initial Adhesion Strength, N/mm ²	≥ 1,0

Packaging and Storage

- Packaged in a 10-litre plastic container.
- The shelf life is 1 year from the date of manufacture when stored unopened in its original packaging in a dry, frost-free environment.

Warnings

- Application is recommended at temperatures between +5 °C and +35 °C.
- The application surface must be dust-free, dry and clean.
- Protect from frost.
- Wash all tools with water after application.
- Harmful if swallowed.

Document No: TDS.ENG.07.08

Revision No: 1

Document Revision Date: 20.08.2026

Liability: Above stated data obtained in lab conditions. Entegre will not be liable for any defect in product occurring by reason of events or conditions not within its control such as misuse, mishandling, improper storage or improper installation. Entegre reserves the right to revise the information contained herein without prior notice.



Hüseyinli Mah. Beykoz Cad.
No: 222/4 Çekmeköy - İstanbul

+90 (0216) 434 50 96

export@entegreharc.com.tr

Page 1

 ENTEGRE

"Building Life"

PRIMEL SL®

Adhesion-Enhancing, Defoaming Floor
Preparation PrimerCOMPLEMENTARY AND
AUXILIARY PRODUCTS

- Keep out of reach of children.
- Keep in a tightly closed container.
- Avoid contact with eyes and skin.
- Please consult us regarding all other application conditions and technical questions.

Conformity Documents



TS 13744 / March 2017

Class 2: Filler-Free Adhesion-Enhancing Primer

Document No: TDS.ENG.07.08

Revision No: 1

Document Revision Date: 20.08.2026

Liability: Above stated data obtained in lab conditions. Entegre will not be liable for any defect in product occurring by reason of events or conditions not within its control such as misuse, mishandling, improper storage or improper installation. Entegre reserves the right to revise the information contained herein without prior notice.



Hüseyinli Mah. Beykoz Cad.
No: 222/4 Çekmeköy - İstanbul

+90 (0216) 434 50 96

export@entegreharc.com.tr

Page 2