



Fields of Application

A filled, resin-based concrete primer with special polymer additives, used to increase surface adhesion before the application of gypsum- and cement-based plasters on exposed concrete walls and ceilings.

Properties

- The special resin in its formulation increases the adhesion strength of the plaster to be applied.
- It prevents rapid water loss from the plaster, thereby extending the plaster's working time.
- It facilitates plaster application, saving time and labour.

Application

Surface Preparation

The surface must be dry, sound, clean and free from oil.

Mixture Preparation and Application

For use beneath plaster, dilute at a ratio of 1:3:

- 4 kg Water / 12 kg PRIMEL 606 must be diluted with water before use. The specified amount of water is the maximum value; if desired, the product may also be used at a thicker consistency. Mix PRIMEL 606 with the specified amount of water until homogeneous. During application, stir the diluted primer from time to time. Apply PRIMEL 606 to the surface using a roller or brush.

Apply the plaster once the material can no longer be scratched off the surface with a fingernail.

Consumption

150-200 g/m²

Technical Values

Density, kg/L	~ 1,45
Colour	Pink
pH	7,0 – 9,0
Application Thickness, mm	Max. 2
Initial Bond Strength, N/mm ²	≥ 1,0
Drying Time, min (20 °C and 50% Relative Humidity)	60-120
Temperature Resistance, °C	-20 / +80

Packaging and Storage

- Packaged in 12 kg plastic buckets.
- Store in enclosed areas away from direct sunlight.
- The shelf life is 1 year from the date of manufacture when stored unopened in its original packaging in a dry, frost-free environment.

ENTEGRE

"Building Life"

PRIMEL 606® BETOKONTAK

Adhesion-Enhancing Synthetic Resin
Dispersion Primer Applied Prior to
Gypsum- and Cement-Based Plaster
Applications



COMPLEMENTARY AND
AUXILIARY PRODUCTS

Warnings

- Application is recommended at temperatures between +5 °C and +35 °C.
- Provided that the container is kept closed, the product must be used within 3 days after dilution.
- The application surface must be dust-free, dry and clean.
- Protect from frost.
- All tools used must be washed and cleaned with water after application.
- Harmful if swallowed.
- Keep out of reach of children.
- Keep in a tightly closed container.
- Avoid contact with eyes and skin.
- Please consult us regarding all other application conditions and technical questions.

Certificate of Conformity



TS 13744 / March 2017

Class 1: Adhesion-Enhancing Primer Containing Filler
Material

Document No: TDS.ENG.07.07

Revision No: 1

Document Revision Date: 20.08.2026

Liability: Above stated data obtained in lab conditions. Entegre will not be liable for any defect in product occurring by reason of events or conditions not within its control such as misuse, mishandling, improper storage or improper installation. Entegre reserves the right to revise the information contained herein without prior notice.



Hüseyinli Mah. Beykoz Cad. No: 222/4 Çekmeköy - İstanbul
+90 (0216) 434 50 96
export@entegreharc.com.tr